(0) 6370556.URPN.
(9) ("3979701" | "4027147" | "4422156" | "5025406" | "5166895" | "5383145" | "5481316" | "550087...
(9) ("3979701" | "4027147" | "4422156" | "5025406" | "5166895" | "5383145" | "5481316" | "550087...
(3) 9517708.pn.
(753) difference adj squar$3
(27) 32.ti.
(3313) difference near1 squar$3 not 32.ti.
(3340) difference near1 squar$3
(27) 35.ti. not 32.ti.
(23975) decod$3 near5 instruction$1
(731631) square$1 or squaring
(20) (decod$3 near5 instruction$1) with (square$1 or squaring)
(73) 708/606.ccls.
(4) (decod$3 near5 instruction$1) and 708/606.ccls.
(2359) (decod$3 near5 instruction$1) and (square$1 or squaring)
(731631) 37same (square$1 or squaring)
(83) (decod$3 near5 instruction$1) same (square$1 or squaring)
(37458) square$1 adj root
(49) ((decod$3 near5 instruction$1) same (square$1 or squaring)) not (square$1 adj root) not
(38) (((decod$3 near5 instruction$1) same (square$1 or squaring)) not (square$1 adj root)) not (...

Search Browse Queue Clear
DBs USPAT, US-POPUB, EPO, JPO, DERWENT, IBM_TI Plurals
Default operator: OR Highlight all hit terms initially

66.ti.

	U	1	Document ID	Issue Date	Pages	Title	Current(OR)	Current XRef	Retrieval Cl	
13			GB 2293732 A	20030114	76	Viterbi decoder for QAM signal calculations - inputs I and Q channels, and determines Euclidean distance between point on I and Q axes and received			NAKA	
14			JP 03241948 A	19911029	7	Digital video tape recorder - reproduces data according to Euclidean distance between each point in I-Q plane of reproduced signal and reference				
15			JP 04190466 A	19920708	6	Device for representing digital colour image by confined colours - allocates representative colour with minimum three dimensional Euclidean distance				
16			JP 2003223652 A	20030808	7	Video reproduction method involves calculating Euclidean distance of three-dimensional data and index information of frames before and after				
17			JP 59025479 A	19840209	9	Digital superimposed edge generator for TV signal processing - produces edge in accordance with euclidean distance between raster position and				
18			JP 62261293 A	19871113	6	Image data to viotex data conversion method - performs colour coordinate conversion according to euclidean distance in space NoAbstract Dwg 2/3				
19			JP 63040427 A	19880220	6	PSK modulation for satellite communication - controls transmission phase so that Euclidean distance to all error paths becomes longest NoAbstract Dwg				
20			KR 2000045642 A	20020703	1	Method and apparatus for mapping symbol using Euclidean distance and hamming distance - NoAbstract			CHA,	
21			KR	20000816	1	Method for maintaining Euclidean distance between codes of codebook -			KIM,	

Ready
NUM

Pending
Active
L1: (4) (("6453407") or ("6249608")).PN.
L64: (2) (("6601160") or ("6604169")).PN.
L65: (110) ("3781810" | "4398244" | "4472788" | "4481576" | "4488252" | "4511990" | "4556938" |...
L66: (3222) euclidean adj distance
L67: (40) 66.ti.
Failed
Saved
(10241) timeshare$1 or time adj share$1
(76) (timeshare$1 or time adj share$1) near10 correlat$3
(0) 3.ti.
(17) 3.ab.
(502) 708/422-426.ccls.
(7) ((timeshare$1 or time adj share$1) near10 correlat$3) and 708/422-426.ccls.
(6) ("3626168" | "3842252" | "3983379" | "4035802" | "4158234" | "4161033").PN.
(9) 4404645.URPN.

Search List Browse Queue Clear
DBs USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB Plurals
Default operator: OR Highlight all hit terms initially

66.ti.

	U	1	Document ID	Issue Date	Pages	Title	Current OR	Current XRef	Retrieval Cl	
1			CN 1403057 A	20030319	NA	3D Euclidean distance transformation process for soft tissue display in CT image			TIAN,	
2			DE 10008543 A	20030618	10	Encoding method for receiver with folding decoder involves allocating encoding channel bits to subsets and selecting mappings with largest			ENGE	
3			DE 10223808 A	20031218	16	Decoding method for complementary code keying (CCK) signals with correlation of reception frequency in butterfly appliance in first step, and			NITSC	
4			DE 19912825 C	20000810	14	Method of detecting data symbols for mobile radio systems, e.g. GSM systems - involves associating constellation point with lowest Euclidean			SCHR	
5			EP 1143624 A	20030418	21	Reed-Muller code decoder detects minimum Euclidean distance between encoder output and Reed-Muller code supplied to arithmetic operation unit			MUKA	
6			EP 1168855 A	20020102	7	Telecommunications system frequency/frequency combination detection system having operation estimation filter and least mean square algorithm			CHAR	
7			EP 619666 A	20030109	12	Rotationally invariant trellis coded modulation e.g. for modem - selecting subset of multi-dimensional QAM constellation from output of trellis encoder,			WEI,	
8			EP 703568 A	19960327	11	Speech recognition system with reduced recognition response time - determines euclidean distance between input and reference patterns to			HIRA	
9			EP 758467 B	19951116	19	Electronic circuit for determination of Euclidean distance between reference and data points - uses analog input voltages, representing reference point			COLL	
10			FR 2824689 A	20021115	39	Public video phones object extraction process having initial image real time evaluated calculation euclidean distance background/current image and			BOUT	

Ready NUM